

**EZCast Pro Series**
**QuattroPod Series**
**EZCast Pro Dongle II**
**EZCast Pro Box II**
**Cast Go!**


Recommended for	Small meeting rooms	All meeting rooms	Small meeting rooms
Maximum Resolution	4K / 30fps	4K / 30fps	4K / 30fps
App / Software required for complete functionality	Yes	Yes	No
Receiver / Transmitter Interface	Software	Software	Hardware Transmitter / Software
Max. number of transmitters	32	32	32
CPU (for Cast Go: Receiver / Transmitter)	AM8270	AM8270	AM8270 / AM8360D
DRAM (for Cast Go: Receiver / Transmitter)	DDR3 1 GB	DDR3 1 GB	DDR3 512 MB / 64 MB
Power Supply (for QuattroPod Lite: Receiver / Transmitter)	DC-in 5V 1.5A	DC-in 5V 2A	DC-in 5V 1.5A / DC-in 5V 0.9A
USB Charger included	No*	Yes	No*
Operating Systems: Windows / macOS / iOS / Android / Chrome OS / Linux	Yes	Yes	Yes
Compatible with any display or projector	Yes	Yes	Yes
Touch Back Support	No	Yes (via Miracast or EZCast Pro Software)	No
ProCast (broadcast to up to 8 projectors / displays simultaneously)**	Yes	Yes	No
Castcode pin security	Yes	Yes	Yes (via Miracast)
Wi-Fi Standard	5 GHz   802.11ac 2T2R single band 866 MBit/s authentication protocol WPA2-PSK	5 GHz   802.11ac 2T2R single band 866 MBit/s authentication protocol WPA2-PSK	5 GHz   802.11ac 2T2R single band 866 MBit/s authentication protocol WPA2-PSK
LAN	No	1 GBit/s	No
Wireless range (Line of Sight)	Up to 10 meters	Up to 30 meters	Up to 10 meters
PoE	No	Yes	No
Easy integration in large network infrastructures	Limited	Yes	Limited
Simultaneous Casting (Split Screen up to 4 screens, Cast Go up to 2 screens)	Yes	Yes	Yes
BYOD support without additional app/software for Apple AirPlay, Google Cast and Miracast	Yes	Yes	Yes
App for Android	Yes	Yes	Yes
App for iOS	Yes	Yes	No
Software for Windows / macOS	Yes	Yes	No
AirView via EZCast Pro Software / Web browser (broadcast to up to 64 device a picture every 5 sec.)	Yes	Yes	No
Moderator (Host) Control	Yes	Yes	No
Mounting option via VESA	No	VESA 50 x 50	No
Central Management System (Software Windows/macOS)	Yes	Yes	Yes
Dimensions in mm (W x D x H) (for QuattroPod Lite: Receiver / Transmitter)	87,5 x 32 x 12 (without HDMI port)	120 x 80 x 25 (without antenna)	87,5 x 32 x 12 (without HDMI port) / 65 x 32,5 x 12 (without HDMI port)
Weight in g without accessories (for QuattroPod Lite: Receiver / Transmitter)	30	146	30 / 20
Manufacturer	Winner Wave Limited, Taiwan	Winner Wave Limited, Taiwan	NimbleTech Digital Inc., Taiwan

**Product Comparison**

STÜBER SYSTEMS GmbH  
Grabbeallee 31  
D-13156 Berlin  
Germany  
+49-30-23256-1900  
hello@stueber.de  
[www.ezcastpro.eu](http://www.ezcastpro.eu)

\* Sold separately

\*\* An EZCast Pro Dongle II or EZCast Pro Box II is required for each display/projector

© STÜBER SYSTEMS GmbH, Updated May 2024