

Wireless Presentation

For Windows, iOS, macOS, Android, Chrome OS & Linux

Up to 4K* without software or app




The best value model of the QuattroPod series

Casting with transmitter

QuattroPod Lite is a wireless display solution for sharing laptops and mobile devices to a presentation screen or projector. It consists of a receiver and a transmitters. The receiver is connected to a screen or projector via HDMI. The transmitter connects to your PC, notebook or MacBook via **HDMI**. Your device screen will be mirrored to the display automatically. The transmitter supports screen mirroring resolutions of up to Full-HD.





Casting without transmitter

QuattroPod Lite supports screen mirroring using the popular streaming protocols **Apple AirPlay**, **Miracast** and **Google Cast**. For added security activate the optional Security Code feature. **In all three cases this means you do not need to install any app or software and resolutions of up to 4K are supported**.

Touch Back

Touch Back is a feature allowing you to wirelessly interract with a participant's computer via the touch screen of your display. Touch gestures of up to 10 finger gestures are supported **via the wireless transmitter on a Windows or macOS computer**.





The Package

The QuattroPod Mini Package contains 1 receiver and 1 transmitter. The distance between transmitter and receiver with no intermediate walls can be up to 30 meters.

For all devices

No matter whether **PC**, **Notebook**, **Tablet or Smartphone**: QuattroPod Lite supports all devices including Windows, macOS, iOS, Android, Chrome OS and Linux.

4K (Ultra-HD)

4K pictures and videos are no problem. Resolutions up to 3840 x 2160 pixels are supported by QuattroPod Lite receiver.

AirPlay + Miracast + Google Cast

You can even share your iPad, iPhone or macOS device screen content using **Apple AirPlay**. The QuattroPod Lite also supports **Miracast** for Windows-/Android devices as well as **Google Cast**. This means in most cases you do not require the QuattroPod Lite transmitter.

CMS

The Central Management System (CMS) offers central adminstration of all products of the QuattroPod and EZCast Pro II Series.

Documentation

Our comprehensive online documentation covers every aspect of QuattroPod Lite: doc.quattropod.eu.

STÜBER SYSTEMS GmbH

Grabbeallee 31 D-13156 Berlin Germany

T: +49-30-23256-1900 E: hello@stueber.de





Specification

Receiver LR01	
Ports	USB-A, HDMI
Dimensions (W x D x H)	120 mm x 80 mm x 25 mm (without antennas)
Power Supply	DC-in 5V 2A
Tansmitter LT01	
Ports	HDMI
Dimensions (W x D x H)	61 mm x 61 mm x 23 mm (without antenna)
Power Supply	DC-in 5V/0,9A
Allgemein	
Maximum resolution	1920 x 1080 pixels / 60 fps transmitter input 3840 x 2160 pixels / 30 fps receiver output
Wireless standard	5 GHz (802.11ac)
Maximum no. of transmitter	1
Simultaneous splitscreen mirroring	1 transmitter
Authentication protocol	WPA2-PSK
Supported operating systems	Windows 7 / 8 / 10, macOS 10.12 or above, iOS 12 or above, Android 5 or above, Chrome OS, Linux
Security	CE, FCC, BSMI, TELEC, NCC
Manufacturer	Winner Wave Limited, Taiwan

